Polyplaner 450/600

Designed to cut & level:
- Steps in Concrete & Asphalt
- Yellow & White Lines
- Thermoplastic White Lines
  Plastic and Ceramic Road Reflectors

The **Polyplaner 450/600** is a high production carbide asphalt and concrete grinding attachment for line removal.

Ideal for removal of road markings, trip hazards, coatings, epoxies, etching, glue removal and surface preparation.

The easy to use level control ensures the highest accuracy and quality finish.

Side shift lets the machine remove road markings close to structures such as jersey barriers and walls.

Steps up to 70mm can be removed in a matter of minutes.

Schibeci **heavy duty construction** gives long life and minimal servicing.





Below: Polyplaner 450, skid steer mounted



Suits Track Loaders, Skid Steers & Excavators
Accurate, Efficient and Effective
Schibeci Polyplaners are made for tough conditions

Specifications	Polyplaner 450/600
Hydraulic Flow Required	85 to 200 lpm (18 to 44 gpm)
Pressure Range	175 to 230 Bar (2500 to 3300 PSI)
Horsepower Required	30 to 150 KW (40 to 200 HP)
Cutting Width	450 / 600 mm (18 to 24 inches)
Cutting Depth	0 to 10mm (3/8 inch), up to 70mm Steps
Operating Weight	720 kg (1587 lb)
Side Shift	Hydraulic

Features

- Direct Hydraulic Drive
- Compact and Powerful
- High-Speed Cutter Plate
- Quick Change Tooling System
- Independent Level Control
- Floating Turn Table
- Adjustable Level Control Gauges
- Interchangeable Wear Strips on Skid Plates
- Water Spray Bar
- Dust Suppression Port
- Enclosed Cutter Housing to Aid Dust Suppression
- All Removal Tools Supplied with the Machine
- Safety and Operations Manual Provided
- 12 Month Warranty (excluding wear and improper use)





